

EDENHALL E25



**E25 makes your harvesting system
more complete!**



"Unload on the go" to be more efficient.
The side gate is adjustable in height.
The E25 can operate together with most sugar
beet harvesters.



With the long discharge elevator it is easy to
unload directly into trucks.
The elevator is adjustable in height and speed
which also makes it easy to make even beet
heaps.

EDENHALL MEK. VERKSTAD AB

253 41 Vallåkra • Tel: +46 42-32 40 50 • Fax: +46 42 - 32 40 69

E-mail: info@edenhall.se • www.edenhall.se

Technical Information:



- E25 can be ordered with unloading elevator mounted to the right or left.
- Can load 25 tons of sugar beets
Tank volume: 44m³
- Unloading time: Approx. 2 minutes
- Unloading height 2 - 4 meter.
- Unloading belt 1850mm wide
- Loading height 3 - 3,6 meter (also depending on tyres and chassi)
- Minimum hp: 180
- Two separate hydraulic systems. All piston functions are connected to the tractor's hydraulic system. Functions regarding unloading are one system driven by PTO-shaft controlled by the buttons on the joystick.
- Beets are unloaded in 3 automatic steps:
 - 1) Unloading belt starts, speed is adjustable.
 - 2) Cross-way floor starts
 - 3) Length-way floor starts
- Mounted on Metsjö's chassi MetaQ 75. E25 can be removed and chassi can be used with other equipments. (See separate leaflet)
- 3 axle chassi for less compaction in the field.



Dealer:

